

WWW.CASABELLAFLOORS.COM

DESIGN, COMMITMENT, AND SUPPLIES YOU CAN TRUST.



CHASSIS® SERIES GLUE DOWN												
SERIES	ITEMS	OVERALL THICKNESS	WEAR LAYER	VA/E A D L IN AITED	PACKAGING							
			Featuring enhanced coating finish	WEAR LIMITED WARRANTY	SF/ CT	PC/ CT	CT/ PA	Weight / CT				
Chassis©	CHA-7477, CHA-7478, CHA-7480, CHA-7481, CHA-7482	2.0 mm	6 mil	20-Year Residential 10-Year Light Commercial	32.72	14	85	25.57 lbs				
Chassis© Advantage	CAD-8917, CAD-8918, CAD-8920, CAD-8921, CAD-8922	2.0 mm	12 mil	30-Year Residential 20-Year Light Commercial	32.72	14	85	25.57 lbs				
Chassis© Pro	CPR-9257, CPR-9258, CPR-9260, CPR-9261, CPR-9262	3.0 mm	20 mil	Lifetime Residential 30-Year Commercial	27.98	12	65	32.88 lbs				

CLASSIFICATION: ASTM F 1700-04 Class III, type A or B Solid Vinyl Floor Tile | CONSTRUCTION: Layered plank consisting of a wear layer, film, and backing | EDGE: Square | INSTALLATION METHOD: Glue down

CHASSIS® SERIES SPC												
SERIES	ITEMS	OVERALL THICKNESS	WEAR LAYER		PACKAGING							
			Featuring enhanced coating finish with anti-bacterial protection	WEAR LIMITED WARRANTY	SF/ CT	PC/ CT	CT/ PA	Weight / CT				
Chassis© Pro SPC Plus	CHS-5480CB, CHS-5481CB, CHS-5482CB, CHS-5487CB, CHS-5488CB	5.0 mm (4 mm + 1 mm cushion backing)	20 mil	Lifetime Residential 30-Year Commercial	28.84	12	45	49.45 lbs				
Chassis© Advantage SPC Plus	CAS-3802CB, CAS-3803CB, CAS-3804CB, CAS-3807CB, CAS-3808CB	4.5 mm (3.5 mm + 1 mm cushion backing)	12 mil	30-Year Residential 20-Year Light Commercial	28.84	12	55	42.88 lbs				

CLASSIFICATION: ASTM F-3261-17 Resilient flooring in modular format with Solid Polymeric Core | CONSTRUCTION: ABA SPC | INSTALLATION METHOD: Angle/Angle

\* All measurements are nominal.



ARMATURE



**BACKBONE** 



**SUSPENSION** 



**MOTORCOACH** 



SPITFIRE



